

ART 34 ANDT

-1-

WATERCRAFT

This invention relates to a watercraft which may be used for sailing using wind power, but which can maintain a level trim when mechanically propelled at high speeds.

Sailing craft can be provided with a displacement mono-hull with a transverse cross-section which tapers downwardly on each side to its keel line, and which increases in cross-section from the bow to a fullest transverse section, and decreases in cross section from the fullest transverse section to the after end. Such a mono-hull shape is suitable for sailing because of its streamlined longitudinal shape when upright and when heeled over.

However, displacement mono-hulled sailing craft as described above are not suitable to be mechanically propelled at high speeds. When mechanical propulsion means, for example an outboard motor or a screw, provide high levels of forward thrust to the after end of the hull, the bow is forced out of the water and the aft sinks lower into the water. This slows the craft because its forward facing profile is increased, which results in a greater resistance against the water. The more power which is provided to the after end of the hull, the greater the bow lift and the water resistance. As a result the maximum speed which can be reached is fixed, regardless of the size of the engine. The object of the present invention is to overcome some of these problems and provide a watercraft with a displacement hull which may be used for sailing and be mechanically propelled at high speeds.

According to the present invention a watercraft for sail and mechanical operation provided with a displacement

ART 34 AMDT

-2-

hull and a keel, is provided with hydrofoil means adapted to only provide lift to the after end of the hull.

The hydrofoil means can comprise a flat hydrofoil element, which is attached in a transverse arrangement by struts to the bottom of the after end of the hull of the watercraft. When the craft is propelled at a high speed the angle of the hydrofoil is set to provide the optimum level of lift to the aft to maintain the optimum trim level for the particular speed of the craft.

As the speed of the craft changes the angle of the hydrofoil element can be adjusted, either manually or automatically, to provide the optimum level of lift to the aft to maintain an optimum trim level at any speed.

Preferably the watercraft is mono-hulled with a transverse cross-section which tapers downwardly to its keel line, and which increases in cross-section from the bow to a fullest transverse section, and decreases in cross section from the fullest transverse section to the after end. The keel line of the hull tapers downwardly from the bow and the stern to a base line at the fullest transverse section.

The craft can be provided with a drop, or a swing, keel, which is lowered into position to provide ballast when the craft is sailing, and is raised to reduce drag when the craft is propelled mechanically. Further, the craft can also be provided with internal water ballast tanks which can be filled with water to provide ballast when sailing, and emptied to reduce the displacement when the craft is propelled mechanically.

ART 34 AMDT

-3-

When the craft is being powered by its sails the hydrofoil is set level to the water flow under the after end of the hull so zero lift and minimum drag are provided and the hull operates as normal. It has been found that the hydrofoil provides stability to the hull when the craft is being sailed and acts as a damper in rough conditions, which are additional benefits

In one construction the hydrofoil is disposed approximately level with the base line of the hull. However, in another construction the hydrofoil is disposed approximately level with the base line of the drop keel. It has been found that with either of these arrangements when the craft is grounded or removed from the water it can be supported in an upright position by the lowest point of the hull or the keel and the hydrofoil, like a tripod, which is an additional benefit.

Preferably the hydrofoil element is attached to the bottom of the hull by two struts. The hydrofoil element can be substantially rectangular in shape, with the shorter sides thereof disposed substantially parallel to the direction of the hull. Further, the hydrofoil element can have a streamlined cross-section with an elongated tear-drop shape, which passes through the water with the least drag.

In one construction the struts are provided with rudder elements adapted to steer the craft. The rudder elements can be fixed aft of the struts, can be provided as part of the struts, or the struts can be the rudder elements. With this arrangement a traditional rudder is not required for the craft, which further reduces drag.

The watercraft can be propelled by an inboard engine, preferably provided with a screw. The screw can have a known

ART 34 AMDT

-4-

type of blades which can be rotated to be parallel with the direction of the hull to reduce drag when sailing.

In a preferred construction the hydrofoil element can be rotated from a zero lift angle level with the water flow under the aft end of the hull, to a lift angle of approximately -5 to -8 degrees.

The upper hull of the watercraft can be shaped with a spray rail feature to shield the operators from wash produced at high speeds.

The system can be used on any watercraft, but in a preferred construction the invention is applied to a 13 metre ocean-going yacht, with about 6 berths.

The invention also includes a hydrofoil element for use with a watercraft for sail and mechanical operation provided with a displacement hull and a keel, which is adapted to only provide lift to the after end of the craft.

The invention can be performed in various ways but one embodiment will now be described by way of example and with reference to the accompanying drawings in which:

Figure 1 is a perspective view of a boat hull according to the present invention;

Figure 2 is a perspective view of another boat hull according to the present invention;

Figure 3a is a diagrammatic front view of the cross sectional contours of the hull shown in both Figures 1 and 2;

ART 34 AMDT

-5-

Figure 3b is a diagrammatic side view of the hull shown in Figure 3a with the cross-sectional lines;

Figure 4 is a side view of a yacht according to the present invention, arranged for sail operation;

Figure 5 is a side view of the yacht shown in Figure 4 arranged for motorised operation;

Figure 6a is a diagrammatic front view of the cross sectional contours of the hull shown in both Figures 4 and 5; and,

Figure 6b is a diagrammatic side view of the hull shown in Figure 6a with the cross sectional lines.

Figure 1 shows a displacement boat hull 1 which is shaped for sailing and is approximately 13 metres in length. Figures 3a and 3b show the cross-sectional contours of the hull 1. The hull 1 has a broad beam to provide sufficient righting moment to support the sails and provide an adequate lever arm for internal water ballast. In other respects the hull 1 is shaped for high-speed sailing (approximately 10 knots). As shown in Figure 1 the hull 1 is provided with a drop keel 2 with a ballast bulb 3, and a hydrofoil element 4. The hydrofoil element 4 comprises two struts 5 and an interconnecting horizontal wing 6. The wing 6 is substantially rectangular in shape with the shorter sides thereof disposed substantially parallel to the direction of the hull 1. The hydrofoil element is mounted adjacent to the aft 7 of the hull 1.

ART 34 AMDT

-6-

In Figure 2 displacement boat hull 8 is identical to the hull 1 shown in Figure 1, except for recess 9 provided on the lower surface. Recess 9 is dimensioned to receive the upper section of the ballast bulb 11 when the keel 10 is raised. Further, struts 12 have been provided with rudder elements 13 to steer the craft.

Figures 4 and 5 show a displacement mono-hulled 13 metre sailing yacht 14. Figures 6a and 6b show the cross-sectional contours of the hull 15. This type of yacht is known so further details will not be described here. The yacht 14 has a hull 15 shaped for sailing, a sailing rig 16 and a motorised screw 17. The hull 15 is also provided with a spray rail ledge 18 to protect the operators of the craft from wash at high speeds. (The shape of the spray rail 18 can be better seen in Figures 6a and 6b). The yacht 14 is provided with a hydrofoil element 19 comprising two struts 20 (only one shown) and an interconnecting horizontal wing (not shown). The hydrofoil element is identical to that shown in Figure 2 with rudder elements 21 provided on the struts 20, and it is attached to the bottom of the hull 15, adjacent to the aft 22 of the yacht 14. The yacht 14 is also provided with a drop keel 23 with a ballast bulb 24. The hull 15 also features a recess (not shown) into which the upper section of the ballast bulb 24 can fit when the drop keel 23 is raised.

As shown in Figure 4 the yacht 14 is set for sail operation with the sailing rig 16 arranged to provide propulsion. The wing (not shown) of the hydrofoil element 19 is set level to the water flow under the after end 22 of the hull so zero lift and minimum drag are provided and the hull 15 can operate as normal.

ART 34 AMDT

-7-

As shown in Figure 5 the yacht is set for motorised operation with the sailing rig 16 lowered. The drop keel 23 has been raised and the upper section of the ballast bulb 24 has been received by the recess (not shown) in the bottom of the hull 15. When the screw 17 pushes the yacht through the water at high speeds the wing (not shown) of the hydrofoil element 19 is set at a negative angle and the higher water pressure on the underside of the wing creates lift and holds the yacht 14 at a level trim.

As the speed of the yacht changes the wing is adjusted automatically to provide the optimum level of lift to the aft to maintain an optimum trim level. It will be appreciated that the speed of the yacht can be changed by engine speed as well as sea and weather conditions and any angle of turn, so the wing can be set to respond to these changes to maintain a level trim. It will also be appreciated that the correct wing angles required at high speeds will depend on the size, displacement and engine capacity of the craft with which is it used.

The yacht 14 can be provided with internal water ballast tanks on each side of the hull 15 approximately amidships, in order to provided extra righting moment during sailing. The tanks can be filled automatically when the yacht 14 is in sailing mode, as shown in Figure 4, and then emptied to reduce weight and displacement when the yacht 14 is in motor mode, as shown in Figure 5.

The spray rail 18 protects the occupants of the yacht 14 from water spray created by the high speed of the yacht 14.

Although the above describes the invention as applied to a displacement mono-hulled craft, it will be

-8-

appreciated that the invention can also be applied to a multi-hulled craft. Further, a hydrofoil wing can be attached to the underside of the aft of a water craft in any appropriate manner, for example by one or three struts. In addition, if desired the hydrofoiling effect can be achieved by a number of hydrofoil wings attached to the underside of the hull in any appropriate manner.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.